

21

ELECTRICAL TOOLS

LONG LIFE SOLDERING IRON



- Suitable for welding in large area and main cables, with different welding nozzles
- High Heat capacity, heat conducting and high efficiency
- Easy-to-change system for heating element

PART #	SIZE	PCS
E9605	80W	8
E9606	100W	8
E9607	150W	8
E9608	200W	6
E9609	300W	6

DIGITAL SOLERING STATION



DIGITAL SOLERING STATION



- Quick Temperature Raising and Returning, max. 350°C heat up in 30 second
- Intelligent temperature control circuit, for working under alternating voltage
- Special design, Endurable

PART #	SIZE	TEMP	PCS
E0602	60-130W	160-480°C	1

LONG LIFE SOLDERING IRON



- Mica heater core.
- Convenient to replace heater core.

PART #	SIZE	HEATER	TIP	PCS
E9601	30W	E9611	E9621	6
E9602	40W	E9612	E9622	6
E9603	50W	E9613	E9623	6
E9604	60W	E9614	E9623	6

Supplementary Soldering Iron Tips

PART #	SIZE	TIPS	PCS
E0621	B		6
E0622	SB		6
E0623	I		6
E0627	1,6D		6

PART #	SIZE	TIPS	PCS
E0628	2,4D		6
E0629	3,2D		6
E0637	K		6
E0638	SK		6

MICA HEATER/TIPS



PART #	SIZE	FOR #	PCS
E9611	30W	E9601	12
E9612	40W	E9602	12
E9613	50W	E9603	12
E9614	60W	E9604	10
E9621	4mm	E9601, 30W	10
E9622	5mm	E9602, 40W	10
E9623	6mm	E9603, E9604, 50W 60W	10

GLUE STICKS



PART #	SIZE	CONTENTS	PCS
E9670	11.2x200mm	6PCS	6

WIRE STRIPPER



- Grooving Range: 12-10,16-14,22-18A.W.G.
- Stripping Range: 10,12,14,16,18,20-22A.W.G.
- Cutting Range: 8-32,10-24,10-32,6-32,4-40A.W.G.

PART #	SIZE	LENGTH	PCS
E5801	8"	200,0mm	6

MICA HEATER



PART #	SIZE	FOR #	PCS
T9605	80W	E9605	6
T9606	100W	E9606	6
T9607	150W	E9607	6
T9608	200W	E9608	6
T9609	300W	E9609	6
T9615	80W	E9605	6
T9616	100W	E9606	6
T9617	150W	E9607	6
T9618	200W	E9608	6
T9619	300W	E9609	6

HOT MELT GLUE GUN



- Pre-heat time:3-5 minute
- Flow rate:8-12g per minute
- CE GS approved

PART #	POWER	VOLTAGE	GLUESTICK	PCS
E9663	40W	230V	11,2mm	6
E9664	60W	230V	11,2mm	6

WIRE STRIPPER



- Grooving Range: 12-10,16-14,22-18A.W.G.
- Stripping Range: 10,12,14,16,18,20-32A.W.G.
- Cutting Range: 8-32,10-24,10-32,6-32,4-40A.W.G.

PART #	SIZE	LENGTH	PCS
E5802	9"	225,0mm	6

SOLDER WIRE



Made of lead-tin alloy, including 63% of lead.

PART #	SIZE	LENGTH	PCS
E9742	17g	1,0mm	12

WIRE STRIPPER




- Stripping Range: 12,14,16,18,20,22,24A.W.G.

PART #	SIZE	LENGTH	PCS
E5803	6"	155,0mm	6

ENDURA®
A Textron Company

AUTOMATIC WIRE STRIPPER



- Reinforced plastic grip, comfortable to use.
- Meet and exceed QB/T 2207-1996.

PART #	SIZE	LENGTH	VIEW
E5811	A Type 0.5-1.2-1.6-2.0	6	
E5812	B Type 1.0-1.6-2.0-2.6-3.2	6	
E5813	C Type 0.9-1.25-2.0-3.5-5.5-8.0	6	

MULTI FUNCTION WIRE STRIPPER



- Stripping Range, 0.5-6mm
- Meet and exceed QB/T 2207-1996.

PART #	SIZE	LENGTH	VIEW
E5821	6-1/2"	170mm	6

MODULAR CONNECTOR CRIMPING TOOL



- mainly used for electric, internet and wire
- made of High-Grade Alloy Steel, totally hot treated

PART #	SIZE	VIEW
E5815	4P	6
E5816	6P	6
E5817	8P	6


MODULAR CONNECTOR CRIMPING TOOL



- Suitable for 2 in 1 telephone line connector and network line connector.
- Easy to strip wires with cutting and stripping blades.

PART #	SIZE	VIEW
E5825	8"	12

CRIMPING TOOL



- Range: 0.5-1.5, 1.5-2.5, 4-6mm².

PART #	SIZE	VIEW
E5831	9"	6

CRIMPING TOOL



- Range: 0.5, 1.1.5, 2.5, 4, 6mm².

PART #	SIZE	VIEW
E5832	9"	6

CRIMPING TOOL



- Range: 1.73, 6.65, 8.23, 9.14mm².

PART #	SIZE	VIEW
E5833	9"	6

CRIMPING TOOL



- Range: 1, 2.5mm².

PART #	SIZE	VIEW
E5834	9"	6


CRIMPING TOOL



- Range: 0.5-1.5, 2.5, 4, 6 mm².

PART #	SIZE	VIEW
E5835	9"	6

CRIMPING TOOL



- Range: 0.15-0.5, 0.5-1.5, 1.5-2.5, 4-6 mm².

PART #	SIZE	VIEW
E5836	9"	6

CRIMPING TOOL



- Range: 0.5, 1.1, 1.5, 2.5, 4, 6, 10mm².

PART #	SIZE	VIEW
E5837	9"	6

CRIMPING TOOL



- Range: 6, 48, 5, 36, 3, 24, 1, 64, 9, 1 mm².

PART #	SIZE	VIEW
E5838	9"	6

DETECTING SCREWDRIVER



- Blade made of Cr-V, 100-500V AC.
- With clip.
- Super-long life Neon bulb can be used over 20,000 times.

PART #	SIZE	LENGTH	VIEW
E6751	140mm	140,0mm	12
E6752	190mm	190,0mm	12

DIGITAL DETECTING SCREWDRIVER



PART #	SIZE	VIEW
E6755	135,0mm	12

SHARP HEAD TWEEZER



- Made of stainless steel.

PART #	SIZE	LENGTH	VIEW
E9712	SHARP	125,0mm	12

EXTPA SHARP LONE HEAD TWEEZER



- Made of stainless steel.

PART #	SIZE	LENGTH	VIEW
E9713	Specil Sharp Tip	135,0mm	12

EXTPA SHARP SHORT HEADTWEEZER



- Made of stainless steel.

PART #	SIZE	LENGTH	VIEW
E9714	Short Tip	120,0mm	12

WIDE HEAD TWEEZER



- Made of stainless steel.

PART #	SIZE	LENGTH	VIEW
E9715	Wide Tip	120,0mm	12

SLIGHTLY SHARP HEAD TWEEZER



- Made of stainless steel.

PART #	SIZE	LENGTH	VIEW
E9716	Micro Sharp	115,0mm	12

CVRVED HEAD TWEEZER



- Made of stainless steel.

PART #	SIZE	LENGTH	VIEW
E9717	Bent	118,0mm	12

AUTO VOLTAGE TESTER



PART #	SIZE	LENGTH	VIEW
E6756	6V-12V-24V	135,0mm	12

DIGITAL MULTI-METER



DC Voltage: 200mV/2V±0.5%, 2/20/200V/600V±0.8%
 AC Voltage: 200/600V±1.2%
 DC Current: 20µ/200mA±1.2%, 200µ/2mA/20mA±1.0%, 10A±2.0%
 Resistance: 200Ω±1.0%, 2KΩ/20KΩ/200KΩ±0.8%, 2MΩ±1.2%
 Diode Test: Test Condition: Voltage, approx. 2.8V
 Max. Show Value: 1999 (3 1/2) with automatic polarity indication LCD Display.
 Measuring Method: Dual-slope integration A/D converter system, Overrange Indication: "1"
 Reading Rate: approx. 2-3 times/sec
 Operating Temperature: 0°C-40°C, ±5% R.H.
 Storage Temperature: -10°C-50°C, ±5% R.H.
 Dimension: 138x70x28mm

- Insulated panel,
- Meet and exceed IEC1010-1 CAT III 600V , CAT III 600V.
- Max Transient Voltage: 400V

PART #	SIZE	LENGTH	WEIGHT
E9231	Battery 9V	115g	6

DIGITAL CLAMP METER



- Mini design, suitable for normal measurement of currency, voltage and resistance
- 6 functions, 8 optional ranges
- Meet IEC1010-1 CAT III 600V
- 2m drop-proof
- Data hold function
- Overload protection
- Battery power display
- Safety Level: CAT III, 3 1/2 digital LCD, max. reading: 1999
- Short-Voltage indicator
- Continuity test function

PART #	SIZE	WEIGHT	LENGTH
E9252	Battery 9v	250g	6

Digital Multi-Meter



DIGITAL MULTI-METER



DC Voltage: 400mV-1000V±(0.5%+3)
 AC Voltage: 400mV-1000V±(1%+3)
 DC Current: 400µA-10A±(1.5%+3)
 AC Current: 400µA-10A±(1.5%+3)
 Resistance: 400Ω-40MΩ±(0.5%+2)
 Capacitance: 50mF-200µF±(2%+2)
 10A Fuse; Diode test; Buzzer.
 Max. Show Value: 3999
 Display Size: 69x43mm
 Dimension: 185x87x53mm

- Auto off and on.
- LED display; easy readout.
- Meet and exceed IEC1010-1 CAT III 600V , CAT III 1000V, CAT III 600V.

PART #	SIZE	WEIGHT	LENGTH
E9241	AAA1.5V	360g	12

DIGITAL CLAMP METER



DC Voltage: 1000V(±1.0%)
 AC Voltage: 750V(±1.2%)
 AC Current: 20-200-1000A(±2.0%)
 Resistance: 2K-200K(±1.0%)
 Diode test: 2.8V/1mA
 Frequency: 2KHz(±2.5%)

- High-tech ASS sealing design
- Meet IEC61010-1
- Apply for testing AC Voltage, AC Currency
- With overload protection
- With back-light display
- Continuity test function with buzzer for resistance and frequency

PART #	SIZE	WEIGHT	LENGTH
E9253	Battery 9V	400g	6

Strongly Recommended Functions



- AC/DC voltage, AC/DC current, resistance, capacitance, diode, frequency, temperature measuring, duty-cycle, auto on and off, data hold, etc., RS232 interface connected with computer to record, analyze, process and print data.

- Advanced plastic-injecting panel, insulated,

- Overload-protection function guarantees safety,

- Manual and automatic measuring

- Big LCD display, easy readout.

- Designed and manufactured strictly according to international Electrotechnical Safety Standard.

DIGITAL MULTI-METER



DC Voltage: 200mV/2V/20V/200V±0.5%/1000V±0.8%
 AC Voltage: 2V/20V/200V±0.8%, 750V±1.2%
 Resistance: 200/20k/200k/2MΩ±0.8%, 20MΩ±1.0%
 DC Current: 2m/20mA±0.8%, 200mA±1.5%, 10A±2.0%
 AC Current: 2mA±1.0%, 200mA±1.8%, 10A±3.0%
 Capacitance: 2n/20n/200n/20µF±4.0%
 Max. Reading: 1999
 Transistor hFE: 1-1000
 Continuity test function
 Diode test

PART #	SIZE	WEIGHT	LENGTH
E9243	Battery 9v	200g	6

PROTECTIVE FUNCTION ANALOGUE MULTIMETER



- Suitable to measure DC Voltage, DC Currency and DC max. 10A, AC Voltage, resistance, transistor, diodes, LED, battery, short-circuit beep and capacitance (2000µF max.)
- DC Voltage: 0.1/0.5/2.5/10/50/250/1000V 7 setting
- DC Currency: 50µA/2.5mA/25mA/250mA/10A 5 setting
- AC Voltage: 10/50/250/1000V 4 setting
- Resistance: 1/10/1k/10k 4 setting
- Battery: 1.5/9V 2 setting
- Capacitance: C1(RX1K) (2000µF); C2: 0.025-0.25µF(3 setting)
- Standard working environment: 23°C±5°C, humidity<75%RH.
- Work environment: 0°C-40°C, humidity<90%RH
- Storage condition: -10°C-50°C, humidity<80%RH
- Dimension: 150(L)x97(W)x36(H)mm
- Capacitor Testing Accessory CT-1 (0.025/0.25/25µF 3 setting)

PART #	SIZE	LENGTH
E9237	Battery 9v	6

CVRVEO BLADE ELECTRICAL KNIFE



- Made of premium grade Mn steel.
- Blade hardness>HRC56

PART #	SIZE	LENGTH
E7021	80mm	121.0mm

DIGITAL MULTI-METER



DC Voltage: 200mV/2V/20V/200V/600±0.7%
 AC Voltage: 200mV/2V/200V/600V±0.8%
 Resistance: 200/2K/20K/200K/2MΩ/20MΩ±1.2%
 Max. Reading: 1999
 Continuity test function
 Diode test

PART #	SIZE	WEIGHT	LENGTH
E9234	Battery 9v	200g	6

STRAIGHT BLADE ELECTRICAL KNIFE



- Made of premium grade Mn steel.
- Blade hardness>HRC56

PART #	SIZE	LENGTH
E7022	80mm	121.0mm

DIGITAL DETECTING SCREWDRIVER



- Can test 5 kind electric tension:12V、36V、55V、110V、220V
- Have Induction test functionality
- LED Panel collaborated with Blue LED bulbs
- Night Vision

PART#	VOLTAGE	LENGTH	PCS
E6754	12-250V	140mm	12

SOLDER ABSORBER



- High efficiency to absorb remaining soldering tin.
- PTFE nozzle withstands high temperature and solvent.

PART #	LENGTH	PCS
E9671	195.0mm	12

SOLDER AID TOOLS



- 1-Brush
- 1 - Fork
- 1 - Awl
- 1 - Scraper
- 1 - Hook
- 1 - Push Bar

PART #	CONTENTS	PCS
E9753	6PCS	12

ESD ADJUSTABLE WRIST STRAP



- Anti-static, adjustable.

PART #	PCS
E9745	12

BATTERY TESTER



- batteries is not necessary.
- be exclusively used in testing battery such as D.C,AA,AAA,6F22
- can display the remaining battery power

PART #	PCS
E9256	6

SOLDER ABSORBER



- Single hand operation.
- PLCC with 20 and 84 feet can be extracted.
- Suitable for PLCC components.

PART #	LENGTH	PCS
E9672	202.0mm	12

VINYL ELECTRICAL TAPE



- Excellent insulation, bear the voltage
- Good stickiness

PART #	SIZE	COLOR	DIAMETER	PCS
E9721	18mmx9m	Black	58,0mm	60
E9722	18mmx9m	Red	58,0mm	60
E9723	18mmx9m	Yellow	58,0mm	60
E9724	18mmx9m	Green	58,0mm	60

BALL



PART #	PCS
E9746	12

IC CLIP



- Heat treated, high elasticity,
- Stainless steel, wrapped with P.V.C. comfortable to use.

PART #	PCS
E9752	12

PLCC EXTRACTOR



- Single hand operation.
- PLCC with 20 and 84 feet can be extracted.
- Suitable for PLCC components.

PART #	PCS
E9751	12

ESD FLUID DISPENSER



- Anti-static

PART #	SIZE	PCS
E9747	60ml	12

ENDURA®
A Textron Company

ENDURA®
A Textron Company